


PC BOARD LAYOUT

Dimensions						
No.	A	B (A+5.1)	C (A+1.7)	D (A+2.9)	E (A+2.3)	F (A+4.1)
2*10P	4.50	9.60	6.20	7.40	6.80	8.60
2*15P	7.00	12.10	8.70	9.90	9.30	11.10
2*40P	19.50	24.60	21.20	22.40	21.80	23.60



Number of Contact
20,30,80 Contact

C 28 0 0 X X -06

Series No.

MATE WITH C2800XX-03
C2800XX-05
C2800XX-07
C2800XX-08

LTR	Part Name	Material	Description	QTY
1	Housing	LCP UL94V-0	+30%GF Initial : 1000M Ohms Min.	1
2	Contact	Brass C2680	Current Rating : 0.5 A Initial : 30m Ohms Max.	XX
3	Fitting Nail	Brass C2680	Current Rating : 0.5 A Initial : 30m Ohms Max.	2
4	Mylar	PI	—	1

Temperature Rating : -40°C ~ +105°C.
Dielectric Withstanding Voltage : 300 V AC/Min

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM	TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 P.L.C	± -
1 P.L.C	± 0.30
2 P.L.C	± 0.20
3 P.L.C	± 0.15
ANGLES	± - ±.3°



MATERIAL	SEE NOTE	FINISH	SEE NOTE
CUSTOMER DRAWING			

CHUFON TECH CO., LTD

BTOB PH0.5 H3.4 LCP料 斷差型母座

SIZE	QAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C280000-06	—

CUSTOMER DRAWING	SCALE	SHEET	REV
—	—	1 of 1	AO