



L/IR	Part Name	Material	Description	QTY
1	Housing	LCP UL94V-0	+30%CF 260°C for 10 Seconds. Initial : 1000M Ohms Min.	1
2	Contact	Bronze CS191	Current Rating : 0.5 A Initial : 30m Ohms Max.	XX
3	Fitting Nail	Brass C2680	Current Rating : 0.5 A Initial : 30m Ohms Max.	2

Temperature Rating : -40°C ~ +105°C.
Dielectric Withstanding Voltage : 300 V AC/Min

Circuit No.	Dimensions						
	A	B (A+1.65)	C (A+1.0)	D (A+2.3)	E (A+5.1)	F (A+2.9)	G (A+4.1)
2*10P	4.50	6.15	5.50	6.80	9.60	7.40	8.60
2*15P	7.00	8.65	8.00	9.30	12.10	9.90	11.10
2*20P	9.50	11.15	10.50	11.80	14.60	12.40	13.60
2*30P	14.50	16.15	15.50	16.80	19.60	17.40	18.60
2*40P	19.50	21.15	20.50	21.80	24.60	22.40	23.60

Number of Contact
20,30,40,60,80 Contact

Series No.
MATE WITH C2800XX-01
C2800XX-04
C2800XX-06

C 28 0 0 X X -05

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM	TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 P.L.C	± -
1 P.L.C	± 0.30
2 P.L.C	± 0.20
3 P.L.C	± 0.15
4 P.L.C	± - ±.3'
ANGLES	± - ±.3'



CHUFON TECH CO., LTD

PH0.5 BTOB H3.55 公座 SMT

MATERIAL	SEE NOTE	FINISH	SEE NOTE	WEIGHT	CUSTOMER DRAWING	SIZE	QAGE CODE	DRAWING NO	RESTRICTED TO
						A3	00779	C280000-05	
SCALE						1	SHEET		1 OF 1
REV						AO			